

码头专用油管

A4-238



应用:

■ 软管的波纹状外层使其具有石油输送所需要的柔韧性。内层胶多种配方, 可以根据所输送的物质的不同来设计软管的内胶。

Applications:

■ Built with a corrugated cover to provide flexibility in petroleum transfer service. A variety of tube compounds are available to tailor the chemical and hydrocarbon resistance of the hose to the type of material handled.

技术参数:

- 内层: 丁腈橡胶: 可输送芳香类成份达50%的石油
或氟橡胶: 可输送含芳香类物质达100%的石油
- 增强层: 高强度合成纤维缠绕层及带2根金属螺旋丝
- 外层: 黑色的波纹状的Wingprene橡胶外层
- 温度: -32° C 至 +93° C

Technical description:

- Tube: Nitrile synthetic rubber for up to 50% aromatics. Also available with a Flosyn® tube for up to 100% aromatics.
- Reinforcement: Spiral-ply heavy-duty synthetic fabric with double wire helix
- Cover: Black Wingprene® synthetic cover, corrugated, wrapped finish
- Temperature range: -32°C to +93°C

码头专用油管 FLEXDOCK 225

产品编码 No.	内径 in mm	外径 mm	工作压力 bar	耐负压 in.	弯曲半径 mm	重量 kg/m	
A4-238-3000	3	76.2	98.8	15.5	29	279	4.88
A4-238-4000	4	101.6	134.4	15.5	29	381	9.38
A4-238-6000	6	152.4	186.4	15.5	29	559	14.14
A4-238-8000	8	203.2	239.5	15.5	29	762	20.55
A4-238-10000	10	254.0	295.4	15.5	29	1016	30.49
A4-238-12000	12	304.8	348.5	15.5	29	1524	37.40

blueFuture

您身边的工业专家