

食品级0.9mm物料PU软管 PL-023



颜色:

- 透明,带有 PU 覆盖层的螺旋状镀锌钢丝加强

温度:

- 40°C/+ 90°C (短时间可耐受 125°C)

特性:

- 聚醚型聚氨酯软管,带有 PU 覆盖层的螺旋状镀锌钢丝加强筋。内壁平滑以保证物料在管内流动顺畅。壁厚均为 0.9 毫米。耐霉菌、耐水解。具有优异的耐臭氧和耐候性能。符合 FDA, EU10/2011。该软管无毒、无味、不含卤素,符合 RoHS 环保指令的要求。螺旋钢丝接地可以排静电,符合 TRB S 2153 的规定。阻燃度符合 UL 94 HB 标准。

应用:

- 食品加工行业、制药行业、割草机和扫地清洁车等需要耐霉菌和耐水解的应用。可用于油脂类食品的输送。

Colour:

- Clear with PU coated grey colour steel spiral

Temperature range:

- 40°C+90°C .We do not recommend SIP cleaning, which can severely impair the hose life.

Features:

- Ether based food grade polyurethane hose reinforced with PU coated high adhesion steel wire. Smooth inside to ensure optimization of flow properties. Constant Wall thickness of 0,9mm forthe whole diameter range. Resistant to microbes and to hydrolysis. Excellent against ozone, and weathers. Suitable to deliver dry food stuffs according to EU 10/2011 and FDA.
- The hose conform to RoHS regulations. It can be made antistatic in accordance with TRB S 2153 regulation by grounding the spiral. Flame retardant according with UL 94HB.

Applications:

- Food processing plants, pharmaceutical industry, and anywhere resistance to microbes is required.

产品编码 No.	内径 in.	mm	壁厚 mm	耐负压 mH2O	弯曲半径 mm	体积 m³	重量 kg/m	包装长度 m
PL-023-1000	1"	25	0.9	5.5	30	0.400	0.200	20
PL-023-1250	1-1/4"	32	0.9	5.5	40	0.055	0.260	20
PL-023-1500	1-1/2"	38	0.9	5.0	40	0.076	0.265	20
PL-023-1580	1-9/16"	40	0.9	5.0	50	0.079	0.280	20
PL-023-1770	*	45	0.9	5.0	50	0.092	0.350	20
PL-023-1970	*	50	0.9	4.0	60	0.101	0.385	20
PL-023-2000	2"	51	0.9	4.0	60	0.108	0.395	20
PL-023-2360	2-3/8"	60	0.9	4.0	70	0.124	0.445	20
PL-023-2500	2-1/2"	63	0.9	4.0	70	0.150	0.480	20
PL-023-2560	2-9/16"	65	0.9	4.0	70	0.155	0.495	20
PL-023-2760	*	70	0.9	4.0	80	0.165	0.610	20
PL-023-2950	*	75	0.9	3.5	80	0.176	0.660	20
PL-023-3000	3"	76	0.9	3.5	90	0.232	0.670	20
PL-023-3150	*	80	0.9	3.5	90	0.254	0.700	20
PL-023-3540	*	90	0.9	2.5	100	0.294	0.785	20
PL-023-3940	*	100	0.9	2.5	120	0.281	0.865	15
PL-023-4000	4"	102	0.9	2.5	120	0.286	0.885	15
PL-023-4330	*	110	0.9	2.5	130	0.315	0.950	15
PL-023-4720	*	120	0.9	2.0	140	0.340	1.030	15
PL-023-5000	5"	127	0.9	2.0	150	0.414	1.265	15
PL-023-5120	*	130	0.9	2.0	150	0.423	1.290	15
PL-023-5510	*	140	0.9	1.5	160	0.514	1.385	15
PL-023-5910	*	150	0.9	1.5	170	0.548	1.485	15
PL-023-6000	6"	152	0.9	1.5	170	0.554	1.500	15
PL-023-6300	*	160	0.9	1.5	180	0.674	1.580	15
PL-023-7090	*	180	0.9	1.0	210	0.864	1.575	15
PL-023-7870	*	200	0.9	1.0	230	1.140	1.745	15
PL-023-8000	8"	203	0.9	1.0	230	1.157	1.770	15
PL-023-8980	*	228	0.9	0.5	260	0.941	1.985	10
PL-023-9840	*	250	0.9	0.5	290	1.179	2.170	10
PL-023-10000	10"	254	0.9	0.5	290	1.197	2.205	10
PL-023-10430	*	265	0.9	0.5	300	1.247	2.640	10
PL-023-11000	11"	279	0.9	0.5	320	1.310	2.780	10
PL-023-12000	12"	305	0.9	0.5	350	1.623	3.030	10