

# PHARMED BPT 泵管

## 06508

Masterflex® 06508-17

PharMed® BPT

### 应用:

细胞和组织培养作业及制药用途, 也适用于光敏样品。

### 技术参数:

- 米色不透明
- 无毒, 非溶血性
- 极低渗透性
- 抗酸、碱、氧化剂和动物油及植物油
- 可热封、可粘合, 可成型
- 温度范围: 静态温度: -51°C至132°C  
动态温度: -20°C至100°C
- 灭菌: 高温高压灭菌、环氧乙烷灭菌或伽马射线灭菌。

### 适用标准及认证:

- USP Class VI 级、欧洲药典 (EP 3.2.9)、FDA 21CFR 177.2600、NSF-51、REACH (无 DEHP) 合规性、RoHS 合规性。

### Applications:

Cell and tissue culture and pharmaceutical use. Also suitable for photosensitive samples.

### Technical Description:

- Beige is opaque
- Non-toxic; Hemolytic
- Extremely low permeability
- Acid, alkali, oxidant and animal oil and vegetable oil resistant
- It can be hot-sealed, glued and shaped
- Temperature range: Static temperature: -51°C to 132°C  
Dynamic temperature: -20°C to 100°C
- Sterilization methods: SIP、ETO、Gamma

### Standard/Approval:

- USP Class VI, European pharmacopoeia (EP 3.2.9), FDA 21CFR 177.2600, nsf-51, REACH (DEHP free) compliance, RoHS compliance.

## PHARMED BPT 泵管

## 06508

产品编码 No.	管号	内径		外径 mm	壁厚 mm
		in	mm		
06508-13	L/S 13	1/32"	0.8	4	1.6
06508-14	L/S 14	1/16 "	1.6	4.8	1.6
06508-16	L/S 16	1/8"	3.2	6.4	1.6
06508-25	L/S 25	3/16 "	4.8	8	1.6
06508-17	L/S 17	1/4 "	6.4	9.6	1.6
06508-18	L/S 18	5/16"	7.9	11.1	1.6
06508-15	L/S 15	3/16"	4.8	9.6	2.4
06508-24	L/S 24	1/4 "	6.4	11.2	2.4
06508-35	L/S 35	5/16"	7.9	12.7	2.4
06508-36	L/S 36	3/8 "	9.6	14.4	2.4
06508-26	I/P 26	1/4 "	6.4	12.7	3.3
06508-73	I/P 73	3/8 "	9.6	16	3.3
06508-82	I/P 82	1/2"	12.7	19.1	3.3
06508-70	I/P 70	3/8 "	9.6	19.1	4.76
06508-88	I/P 88	1/2"	12.7	22.4	4.76
06508-89	I/P 89	5/8"	15.9	25.4	4.76

